

Fuga-Shock Eco

Eco-friendly cleaner, ready to use, for removing residues and stains of epoxy resins, ideal for use in GreenBuilding.

Fuga-Shock Eco has a specific cleaning action that removes residue and stains from ceramic tile, vitrified tile and glass mosaic coverings.



GREENBUILDING RATING®					
		✓		✓	✓
		Water-based formulation		No environmental hazard rating	Non-toxic and non-hazardous
RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS					

PRODUCT STRENGTHS
<ul style="list-style-type: none"> • Flooring and walls • Suitable for use with any kind of tiles • High efficiency

AREAS OF USE
<p>Use To eliminate residues and stains of Fugalite® from tiled surfaces.</p> <p>Substrates: - ceramic and vitrified tiles - glass mosaic</p> <p>Do not use On surfaces that are not resistant to basic agents. On marble and natural stone it is advisable to carry out a test in advance.</p>

INSTRUCTIONS FOR USE
<p>Preparation of substrates The coating materials must first be cleaned to remove any dust. Fugalite® must be fully hardened.</p> <p>Preparation Fuga-Shock Eco is a ready-to-use transparent liquid. Shake the bottle well before opening in order to redisperse the liquid evenly.</p> <p>Application It is advisable to perform a preliminary test before applying it on the entire tiled area. Apply Fuga-Shock Eco evenly to the surface to be cleaned with a rough scrubbing pad and leave it until the dirt to be removed begins to visibly lift; this may take a few minutes or up to 3 – 5 minutes depending on the quantity, the elapsed time after fixing (at least 7 days) and the degree of absorption of the surface. Scrape the surface mechanically with abrasive felt pads. Once cleaned, rinse well and dry carefully. The use of wet vacuum makes the operation easier and ensures the complete removal of residue. In the case of large surface areas, a mechanical buffer with an abrasive felt pad for the removing operation is recommended. Repeat for highly stubborn dirt. Leaving the product to act for more than 5 minutes may result in physical and colour alterations in the grout.</p> <p>Cleaning Residues of Fuga-Shock Eco can be cleaned from tools by rinsing them thoroughly with water.</p>

SPECIAL NOTES

Fuga-Shock Eco is a liquid detergent. Before using the product, it is advisable to hermetically seal all doors, windows, rubber seals, furniture, varnished/painted elements, bathtubs and shower trays made of synthetic materials such as methacrylate, PVC, etc..and any surface that could be attacked through direct contact with the detergent or with vapours.
Leaving the product to act for more than 5 minutes may result in physical and colour alterations in the grout.

ABSTRACT

Remove residues and stains of Fugalite®, from ceramic tiles, vitrified tiles, glass mosaic with an eco-friendly, water-based detergent, GreenBuilding Rating® Eco 3, such as Fuga-Shock Eco by Kerakoll Spa. Apply evenly to the surface to be treated, remove dirt with mechanical means, rinse thoroughly and dry carefully, for an average coverage of 1 ℓ = 10 – 20 m².

TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	Transparent liquid
Specific weight	≈ 1,05 kg/dm³
Shelf life	≈ 24 months in the original packaging
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Pack	bottles 1 ℓ
Water dilution ratios	All ratios
Viscosity	≈ 1540 mPa · s, rotor 2 RPM 50 Brookfield method
pH	≈ 1,4
Temperature range for application	from +5 °C to +35 °C
Waiting time before cleaning with water	≈ 2 – 5 min.
Coverage	≈ 10 – 20 m²/1 ℓ

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e.temperature, ventilation and absorbency level of the substrate and of the materials laid.

WARNING

- **Product for professional use**
- abide by any standards and national regulations
- store and use at a temperature above +5 °C. Protect from frost
- rinse thoroughly all surfaces treated
- do not leave cans or bottles open, even during use
- **wear protective gloves and goggles**
- leaving the product to act for more than 5 minutes may result in physical and colour alterations in the grout
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll India Helpline (Toll Free) 1800-200-6550 - info@kerakollindia.com

The Eco and Bio classifications refer to the GreenBuilding Rating® Manual 2012. This information was last updated in April 2015 (ref. GBR Data Report - 05.15); please note that additions and/or amendments may be made over time by KERAKOLL SpA, for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.