

Aqua-Pur Retard

Eco-friendly retardant additive for water-based varnish from the Aqua-Pur range.

Aqua-Pur Retard increases open time, improving workability and application in critical application conditions.



SLC[®]
TECHNOLOGY



Rating 3

1. It improves the application at high temperatures and on large surfaces
2. Specifically intended for new and existing hardwood floors, dry and difficult woods

- × VOC Low Emission
- ✓ Water Based
- × Solvent ≤ 80 g/kg
- ✓ Low Ecological Impact
- ✓ Health Care

Areas of application

→ Intended use:

Specifically intended for diluting:

- Aqua-Pur Flex
- Aqua-Pur Basic
- Aqua-Pur Basic Rapid
- Aqua-Pur
- Aqua-Pur HPX

Do not use for diluting products not listed above; for diluting more than indicated in the data sheets of the products listed above.

Instructions for use

→ Preparation

The product is ready-to-use.

To dilute water-based base coat and finishing coat varnishes, add 5-10% following necessities and data sheets indications.

→ Application

For diluting Aqua-Pur Flex add up to 10% of Aqua-Pur Retard following necessities and data sheets indications.

Special notes

→ The addition of the aforementioned percentages of Aqua-Pur Retard to the varnishes of


the Aqua-Pur range does not increase the VOC value beyond the limits of Directive 2004/42/EC.

Technical Data compliant with Kerakoll Quality Standard

Appearance	Transparent liquid
Pack	0.5 l plastic bottle
Temperature range for application	from +10 °C to +30 °C
Shelf life	≈ 12 months from the date of production in original and intact packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat

Warning

- Product for professional use
- abide by any standards and national regulations
- respect the dilution ratios suggested in this data sheets and in the data sheet mentioned above
- respect the suggested dilution ratios and do not apply excessive amounts of product
- percentages of Aqua-Pur Retard higher than those indicated may reduce the coverage of the varnishes and lengthen overlay and sanding times
- percentages of Aqua-Pur Retard higher than those indicated and its use in cold periods may compromise the opacity and the final aesthetic appearance of the varnishing
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in June 2023 (ref. GBR Data Report - 06.23); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.