

# Aquastop 120

Flexible NBR waterproof joint for perimeter and fractionizing joints in waterproofing systems. For use under ceramic and vitrified tiles and natural stone. Bonds directly on application.

Aquastop 120 ensures continuous waterproofing even at expansion joints.



1. High elasticity and UV light resistance
2. For internal and external use
3. Ideal for bonding with eco-friendly membranes of Aquastop range
4. Guaranteed waterproofing of all types of non-structural fractionizing and connection joints
5. Alkali-resistant

---

## Areas of application

### → Use

For internal and external use on cement-based substrates, plasterboard and metal for wall-floor connection joints and fractionising joints.

Waterproofing of joints in:

- external surfaces (balconies, terraces)
- standard sanitary environments (kitchens, shower cabinets, bathrooms, saunas).

Do not use to contain, or in contact with strong solvents (ketone, ester, hydrocarbons).

---

## Instructions for use

### → Preparation of substrates

The substrate must be cured, clean, solid and dry. For this purpose, oil, grease, loose parts, previous paint coats, cement slurries or coverings of any type must be removed.

The method used to clean the substrate will depend on the type of surface, sandblasting being the ideal technique.

The edges of concrete joints must be smoothed with a sander to remove any sharp ribbing.

### → Preparation

The joint is ready-to-use. Bond overlapping sections on site using a waterproofing product of Aquastop range.

### → Application

Aquastop 120 can be applied to horizontal and vertical joints. Fixing is performed by bonding the mesh edges.

To bond Aquastop 120, apply the waterproofing product to the already prepared substrate with a trowel. Lay the joint tape with the mesh side printed with the words Kerakoll facing upwards. Apply the second coat of waterproofing product to the fabric. Both the fabric edge and 5-10 mm of the tape must be covered. Where jointing operations involve corners, edges, pipes and drains, use special connection sections (internal corner, external corner, flanges). The different elements must be connected using the waterproof membrane, overlapping the edges by at least 20 mm.

### → Cleaning

Tools used for bonding operations can be cleaned with water while the waterproofing product is still fresh. Once hardened, the product can only be removed mechanically.

**Technical Data compliant with Kerakoll Quality Standard**

Appearance	green tape
Shelf life	unlimited
Pack	50 m rolls
Nature of material	thermoplastic NBR
Section width	≈ 20-80-20 mm (mesh/NBR/mesh)
Thickness	≈ 0.6 mm
Weight	≈ 60 g/m

Values taken at +23 °C, 50% R.H. and no ventilation.

**Performance****HIGH-TECH****Elongation at break:**

- longitudinal	≈ 25%
- transversal	≈ 230%

Resistance to the pressure of water	≤ 3 bar
-------------------------------------	---------

**Maximum tensile strength:**

- longitudinal	> 4.1 N/mm <sup>2</sup>
- transversal	> 9.4 N/mm <sup>2</sup>

Vapour permeability $\mu$	8400
---------------------------	------

**Tensile strength after 28 days with Aquastop Nanoflex:**

- joint-substrate	> 1 N/mm <sup>2</sup>	EN 1348
- joint on joint	> 1 N/mm <sup>2</sup>	EN 1348

Values taken at +23 °C, 50% R.H. and no ventilation.

---

## Warning

- Product for professional use
- abide by any standards and national regulations
- use at temperatures between +5 °C and +35 °C
- protect the tape once laid from being damaged at the site
- in the event of joined tapes, lay floor paving and covering joints on the same axis as the joints on the tape
- where jointing operations involve corners, edges, pipes and drains, use special connection sections
- sections of tapes to be joined must be perfectly clean and dry
- if necessary, ask for the safety data sheet
- for any other issues, contact Kerakoll Customer Care +91-22-2839 5593 / 1800 102 4957 - [info@kerakollindia.com](mailto:info@kerakollindia.com)

The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in May 2024; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.