

Cementoresina® Wall

Coloured finishing product for Cementoresina® Wall vertical coverings. Italian design for living comfort.

Defines the decorative structure and texture of Cementoresina® Wall vertical coverings to be overlaid with Cementoresina® Gel transparent protective agent. For internal use, in domestic and commercial environments. For walls, vertical coatings and coating of basin tops and baths. Available in the 10 Warm Collection colours.



Rating 2

- ✓ Regional Mineral $\geq 30\%$
- × VOC Low Emission
- ✓ Solvent ≤ 5 g/kg
- × Low Ecological Impact
- × Health Care

1. Monopack
2. Two-component, coloured throughout the mass
3. Easily workable with Trowel 2
4. Defines the vibrated texture of Cementoresina® Wall
5. Flexible and tough
6. Improved workability

Areas of application

- Intended use:
 - Cementoresina® Wall continuous covering
- Substrates:
 - Wallzero
- For internal use, on walls and coverings in domestic and commercial environments. Suitable

for coating of showers, Turkish baths, baths, shelves, basin tops and other architectural elements.

Do not use

On floors; outside the Cementoresina® Wall.

Instructions for use

- Preparation of substrates
 - First coat: the Wallzero® support layer must be carefully prepared: sand with a rotating orbital sander (40-grain) and clean well removing any sanding residue. Before the application, check that the Wallzero® layer is perfectly dry and level, that all defects and imperfections of the substrate have been covered, and that the Net 90 reinforcing mesh is not showing.
 - Second coat: the Cementoresina® Wall finishing layer applied as first coat can be overlaid after 14 hours from its initial application. The layer can be overlaid with the second coat even if it is still “tacky” on the surface.

If, when applying the first coat of Cementoresina® Wall, any visible crests or flashes form at the corners, they must be removed by using the spreader blade or a sander with grade 60 sandpaper, taking great care not to break through the first coat so as to make the Wallzero layer visible.

- Preparation

Shake part B in its tin, then pour it into the bucket of part A, following the catalysis ratio part A : part B = 3 : 0.4, mix with care using an electric mixer, with rotation speed of 300 - 600 rotations/minute, and with a helicoidal agitator, until a smooth even coloured mixture is obtained. After carefully mixing for the first time, run a squared-sided trowel along the sides and bottom of the bucket to remove the part that may not have been mixed with part B. After cleaning the trowel in the bucket, mix again with a helicoidal agitator until an even coloured mixture is obtained.

- Application
 - First coat: evenly smooth the product on the Wallzero support layer using small semi-circular movements of the spreader without leaving crests or ridges. Apply the product with the spreader tilted so that the blade can slide on the inert material contained in the product by continuously covering the substrate. Make sure that the Wallzero® support layer is completely covered, paying particular attention to covering corners and edges. The product is spread onto the surface, smoothing the surface with Trowel 2 spreader checking that a coverage of $\approx 0.6 \text{ kg/m}^2$ is maintained to provide a layer on the surface of $\approx 0.5 \text{ mm}$. Avoid creating crests and accumulation of material, in order to reduce the areas in which sanding will be necessary.
 - Second coat: evenly smooth the product on the first coat once it has dried and has been suitably prepared, using small semi-circular movements of the spreader without leaving crests or ridges. The spreader must slide over the preceding layer so that the product is completely smoothed off. The product is spread onto the surface, smoothing the surface with Trowel 2 spreader, specified for the application of Cementoresina® 2 Wall, checking that a coverage of $\approx 0.6 \text{ kg/m}^2$ is maintained to provide a layer on the surface of $\approx 0.4 \text{ mm}$. In corners, avoid creating crests and accumulation of material, in order to reduce the areas in which sanding will be necessary. Check carefully that the whole of the surface has been evenly covered.

- Cleaning

The product can be removed from tools with Keragrip Eco Pulep. After Cementoresina® Wall has hardened it can only be removed mechanically.

Performance

HIGH-TECH

Conformity

compliant

EN 15824

Warning

- Product for professional use
- abide by any standards and national regulations
- apply the product at substrate temperatures from +10 °C
- apply on permanently dry substrates
- protect from direct sunlight and currents of air for the first 6 hours
- do not apply on dirty or loose surfaces
- dispose of as indicated in applicable legislation
- the properties of products exposed to sharp changes in temperature (due to transport,

- storage, building site use, etc.) may be altered (e.g. crystallisation, partial hardening, fluidization, accelerated or delayed catalysis). In most cases, when products are restored to optimal conditions, the original properties will also be restored
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service 01772 456 831 - info@kerakoll.co.uk



The Rating classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in January 2021 (ref. GBR Data Report - 02.21); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.