

# Diluyente 01

Eco-friendly thinner to thin alcohol-based and neoprene organic adhesives.

Diluyente 01 is a mixture of pure solvents which increase the workability and open time of alcohol-based and neoprene adhesives to lay resilient materials and carpeting. Specifically intended to remove adhesive residues and clean equipment.



**SLC**  
TECHNOLOGY



## Rating 1

1. High level of purity and compatibility with alcohol-based and neoprene adhesives
2. Effectively removes any adhesive residues

- × VOC Low Emission
- × Water Based
- × Solvent  $\leq 80$  g/kg
- ✓ Low Ecological Impact
- × Health Care

---

## Areas of application

→ Intended use:

Dilution of solvent adhesives and cleaning of residues of adhesives or paint coatings from tools.

Do not use for diluting water and solvent based paints, primer and waterproofing products, single and two-component reactive adhesives, adhesives dispersed in water.

Specifically intended for the dilution of the following products:

- S45 Extra
- S45
- S45 F

---

## Instructions for use

→ Add up to a maximum of 5% to the products indicated above, following the instructions on the relevant technical data sheets.

→ Remove product residues from the tools and clean with a cloth soaked in Diluente 01. Leave the tools to soak in Diluente 01 if necessary. Carefully dry the tools from the residues of Diluente 01 before using.

---

### Technical Data compliant with Kerakoll Quality Standard


Appearance	Transparent liquid
Pack	10 l drums
Shelf life	≈ 24 months from the date of production in original and intact packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C to +35 °C
Boiling point	+110 °C
Flash point	-5 °C
Density at +20 °C	0.85 g/cm <sup>3</sup>

---

# Warning

- Product for professional use
- abide by any standards and national regulations
- respect the dilution ratios suggested in this data sheets and in the data sheet mentioned above

- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in June 2023 (ref. GBR Data Report - 06.23); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.