



DECLARATION OF PERFORMANCE No 0145

- 1. Unique identification code of the product-type: SUPER-KT ECO
- 2. Intended use/es:

Normal setting cementitious adhesive for ceramic tiling, all internal and external tiling

3. Manufacturer:

KERAKOLL Hellas E.P.E. - 1st km. Schimatari-Avlida Rd. - 32009 Schimatari-Viotia - Greece

- 4. System/s of AVCP: System 3 and System 3 for reaction to fire
- 5. Harmonised standard: EN12004:2007 + A1:2012

Notified body/ies: Modena Centro Prove No. 1599

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Bond strength as: initial tensile adhesion strength	≥ 0,5 N/mm²
Durability for: Tensile adhesion strength after heat ageing Tensile adhesion strength after water immersion	≥ 0,5 N/mm² ≥ 0,5 N/mm²
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Zissis Koulaxidis (General Manager)** At Schimatari-Viotia, on 29/12/2016