



**DECLARATION OF PERFORMANCE No 0419**

1. Unique identification code of the product-type: **H30 GEL**
2. Intended use/es:  
**Improved cementitious adhesive for all internal and external tiling.**
3. Manufacturer:  
**KERAKOLL Hellas E.P.E. - 1st km. Schimatari-Avlida Rd. - 32009 Schimatari-Viotia - Greece**
4. System/s of AVCP: **System 3 and System 3 for reaction to fire**
5. Harmonised standard: **EN12004:2007 + A1:2012**  
Notified body/ies: **Modena Centro Prove No. 1599**  
**Istituto Giordano No. 0407**
6. Declared performance/s:

Essential characteristics	Performance
<b>Reaction to fire</b>	<b>Class A1<sub>fl</sub></b>
<b>Bond strength as: initial tensile adhesion strength</b>	<b>≥ 1,0 N/mm<sup>2</sup></b>
<b>Durability for: Tensile adhesion strength after heat ageing Tensile adhesion strength after water immersion Tensile adhesion strength after freeze-thaw cycles</b>	<b>≥ 1,0 N/mm<sup>2</sup> ≥ 1,0 N/mm<sup>2</sup> ≥ 1,0 N/mm<sup>2</sup></b>
<b>Release of dangerous substances</b>	<b>See SDS</b>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Zissis Koulaxidis (General Manager)**

At Schimatari-Viotia, on 01/12/2019