



kerakoll

DECLARATION OF PERFORMANCE No 0634

1. Unique identification code of the product-type: **SETAFLEX SEMI-RAPID**
2. Intended use/es: **Improved deformable cementitious adhesive with reduced slip for internal and external use**
3. Manufacturer: **Kerakoll UK Ltd, Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK.**
4. System/s of AVCP:
System 3
System 4 for reaction to fire
5. Harmonised standard: **BS EN 12004-1:2017**
Notified body/ies: **Lucideon No. 1289**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class E
Bond strength as: initial tensile adhesion strength	≥ 1,0 N/mm²
Durability for: Tensile adhesion strength after heat ageing	≥ 1,0 N/mm²
Tensile adhesion strength after water immersion	≥ 1,0 N/mm²
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Carl Gardner (Regional Managing Director)**

At Leyland, on 01/06/2024

Kerakoll UK Ltd
Tomlinson Road,
Leyland, PR25 2DY
United Kingdom

+44 (0) 1772 456 831
info@kerakoll.co.uk
www.kerakoll.com

Co Reg. No: 04627336
VAT number GB 636237732