



kerakoll

DECLARATION OF PERFORMANCE No 0571

1. Unique identification code of the product-type: **KLIMAEXPERT System**

Products system components: Keraklima Eco, Klima Air (variante EPS WHITE TR100), Klima Air Black (variante EPS BLACK TR100), Rinforzo V50, Kerakover Eco Acrilex Fondo, Kerakover Eco Kompact

2. Intended use/es: **External thermic insulation of walls and buildings**

3. Manufacturer: **Kerakoll Ibérica, S.A.U. – Ctra. Alcora Km 10,450 Castellón - España**

4. System/s of AVCP: **System 2+**

5. European Assessment Document: **EAD 040083-00-0404, January 2019**

European Technical Assessment:: **ETA-22/0161 of 25/02/2022**

Technical Assessment Body: **ITC CNR**

Notified body/ies: **ITeC n°1220**

6. Declared performance/s:

- Safety in case of fire (BWR 2)

Essential characteristics	Performance
Reaction to fire	
- Reaction to fire of ETICS	Euroclasse B - s2 d0
- Reaction to fire of thermal insulation material	Euroclasse E
Facade fire performance	NPA
Propensity to undergo continuous smouldering of ETICS	NPA

- Hygiene, health and the environment (BWR 3)

Essential characteristics	Performance
Content, emission and/or release of dangerous substances – leachable substances	NPA
Water absorption	
- of the base coat and the rendering system (after 24 h)	
<i>Keraklima Eco</i>	0.170 Kg/m ² 0.091 Kg/m ²
- of the thermal insulation product	W _p ≤ 0.5 kg/m ²
Hygrothermal behaviour	satisfied
Freeze thaw performance	satisfied
Impact resistance	category II
Water vapour permeability	
- of the rendering system	S _D 1.0
- of the thermal insulation product	20-30 μ

kerakoll.com

KERAKOLL IBÉRICA S.A.U. – Carretera de Alcora, km. 10,450 – 12006 Castellón de la Plana – España

Tel. +34 964 251 500 – Fax +34 964 241 100 – e-mail: info@kerakoll.es

C.I.F. A-12331435. Inscrita en el Registro Mercantil de CASTELLÓN, TOMO 594, LIBRO 161, FOLIO 101, HOJA N.º CS 4393, INSC. I.ª SECC. G.



kerakoll

- Safety and accessibility in use (BWR 4)

Essential characteristics		Performance	
Bond strength (dry conditions)			
- between base coat and insulation product	100 Cs	159	151
- between adhesive and concrete	100 Ca	1192	1164
- between adhesive and insulation product	100 Cs	159	151
Tensile strength_EPS (dry conditions)		EPS-EN 13163-TR100	
Shear strength		≥ 20 kPa	
Modulus of elasticity		≥ 1000 kPa	
Bond strength after ageing of finishing coat tested on the rig			
		Failure mode ¹ (%)	Mean value (kPa)
	<i>Insulation and base coat</i>	100 Cs	90
	<i>Insulation/Base Coat/Key Coat/Finishing</i>	100 Cs	80

- Protection against noise (BWR 5)

Essential characteristics	Performance
Airborne sound insulation of ETICS	NPA

- Energy economy and Heat retention (BWR 7)

Essential characteristics	Performance	
	Thickness min (mm)	Thermal resistance (m ² K/W)
<i>Klima Air</i>	40	1.10
<i>Klima Air Black</i>	40	1.30

¹ Cs: Cohesive failure in substrate; Ca: Cohesive failure into adhesive

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia (legal representative)**

At Castellon, on 30/06/2023

kerakoll.com

KERAKOLL IBÉRICA S.A.U. - Carretera de Alcora, km. 10,450 - 12006 Castellón de la Plana - España

Tel. +34 964 251 500 - Fax +34 964 241 100 - e-mail: info@kerakoll.es

C.I.F. A-12331435. Inscrita en el Registro Mercantil de CASTELLÓN, TOMO 594, LIBRO 161, FOLIO 101, HOJA N.º CS 4393, INSC. I.ª SECC. G.



kerakoll

CE 1220	KERAKOLL Iberica S.A.U. Ctra. Alcora Km 10,450 Castellon. España. www.kerakoll.com
22 KlimaExpert KLIMA AIR DoP n° 0571	
ETA-22/0161 EAD 040083-00-0404	

CE 1220	KERAKOLL Iberica S.A.U. Ctra. Alcora Km 10,450 Castellon. España. www.kerakoll.com
22 KlimaExpert KLIMA AIR BLACK DoP n° 0571	
ETA-22/0161 EAD 040083-00-0404	

kerakoll.com

KERAKOLL IBÉRICA S.A.U. - Carretera de Alcora, km. 10,450 - 12006 Castellón de la Plana - España
Tel. +34 964 251 500 - Fax +34 964 241 100 - e-mail: info@kerakoll.es