



## DECLARATION OF PERFORMANCE No. 0338

1. Unique identification code of the product-type: **UNISIL N ISO**
2. Intended use/es: **Sealant for external and internal, non-structural use: facade joints.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:  
**System 3 and System 3 for reaction to fire**
5. Harmonised standard: **EN 15651-1:2012**  
Notified body/ies: **GINGER CEBTP, No. 0074**  
**Laboratoire National de metrologie et d'Essais, No. 0071**
6. Declared performance/s:  
**EN15651-1 F-EXT-INT-CC (Class 25 LM)**  
**Pretreatment: Method A**  
**Substrate: aluminium without primer**  
**mortar M2 without primer**

| Essential characteristics   | Performance     |
|---|-----------------|
| <b>Reaction to fire</b>   | <b>Class E</b>  |
| <b>Resistance to flow</b>   | <b>≤ 3 mm</b>   |
| <b>Loss of volume</b>   | <b>≤ 10%</b>    |
| <b>Tensile properties at maintained extension after water immersion</b>   | <b>Pass</b>     |
| <b>Secant tensile modulus at -30°C</b>  | <b>≤ 0.9MPa</b> |
| <b>Tensile properties at maintained extension for non-structural sealants used in joints in cold climates areas (-30°C)</b> | <b>Pass</b>     |
| <b>Durability</b>   | <b>Pass</b>     |
| <b>Release of dangerous substances</b>  | <b>See SDS</b>  |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 24/05/2022

**www.kerakoll.com**

KERAKOLL FRANCE au capital de € 6.500.000,00  
25 Avenue de l'Industrie - 69960 Corbas, France  
Tél +33 (0) 4 72 89 06 80 - Fax +33 (0) 4 72 89 06 81 - e-mail: info@kerakoll.fr  
Siret 809 032 469 00011



## DECLARATION OF PERFORMANCE No. 0338

1. Unique identification code of the product-type: **UNISIL N ISO**
2. Intended use/es: **Sealant for non-structural use: glazing application**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:  
**System 3 and System 3 for reaction to fire**
5. Harmonised standard: **EN 15651-2:2012**  
Notified body/ies: **GINGER CEBTP, No. 0074**
6. Declared performance/s:  
**EN15651-2 G-CC (Class 25 LM)**  
**Pretreatment: method A**  
**Substrate: glass without primer**  
**aluminium without primer**

| Essential characteristics  | Performance      |
|--|------------------|
| <b>Reaction to fire</b>  | <b>Class E</b>   |
| <b>Resistance to flow</b>  | <b>≤ 3 mm</b>    |
| <b>Loss of volume</b>  | <b>≤ 10%</b>     |
| <b>Secant modulus at -30°C</b>   | <b>≤ 0,9 MPa</b> |
| <b>Tensile properties at maintained extension at -30°C</b>                               | <b>Pass</b>      |
| <b>Adhesion / cohesion properties after exposure to heat, water and artificial light</b> | <b>Pass</b>      |
| <b>Elastic recovery</b>  | <b>≥ 60%</b>     |
| <b>Durability</b>  | <b>Pass</b>      |
| <b>Release of dangerous substances</b>   | <b>See SDS</b>   |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 24/05/2022

**www.kerakoll.com**

KERAKOLL FRANCE au capital de € 6.500.000,00  
25 Avenue de l'Industrie - 69960 Corbas, France  
Tél +33 (0) 4 72 89 06 80 – Fax +33 (0) 4 72 89 06 81 – e-mail: info@kerakoll.fr  
Siret 809 032 469 00011



## DECLARATION OF PERFORMANCE No. 0338

1. Unique identification code of the product-type: **UNISIL N ISO**
2. Intended use/es: **Sealant for non-structural use: sanitary joints.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:  
**System 3 and System 3 for reaction to fire**
5. Harmonised standard: **EN 15651-3:2012**  
Notified body/ies: **GINGER CEBTP, No. 0074**  
**Laboratoire National de metrologie et d'Essais, No. 0071**
6. Declared performance/s:  
**EN15651-3 S (Class XS3)**  
**Pretreatment: Method A**  
**Substrate: aluminium; without primer**  
**mortar M2; without primer**

| Essential characteristics   | Performance    |
|---|----------------|
| <b>Reaction to fire</b>   | <b>Class E</b> |
| <b>Resistance to flow</b>   | <b>≤ 3 mm</b>  |
| <b>Loss of volume</b>   | <b>≤ 20%</b>   |
| <b>Tensile properties at maintained extension after water immersion</b> | <b>Pass</b>    |
| <b>Microbiological growth</b>   | <b>4</b>       |
| <b>Durability</b>   | <b>Pass</b>    |
| <b>Release of dangerous substances</b>                                  | <b>See SDS</b> |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 24/05/2022

**www.kerakoll.com**

KERAKOLL FRANCE au capital de € 6.500.000,00  
25 Avenue de l'Industrie - 69960 Corbas, France  
Tél +33 (0) 4 72 89 06 80 - Fax +33 (0) 4 72 89 06 81 - e-mail: info@kerakoll.fr  
Siret 809 032 469 00011