

kerakoll

DECLARATION OF PERFORMANCE No 0045

- 1. Unique identification code of the product-type: GEOLITE MICROSILICATO
- 2. Intended use/es: Repair products for concrete, used in buildings and civil engineering works according to principles 1 (PI), 2 (MC) and 8 (IR).
- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP: System 2+ and System 3 for reaction to fire
- 5. Harmonised standard: EN 1504-2:2005

Notified body/ies: S.G.S. Italia No.1381

INSTYTUT CERAMIKI I MATERIALOW BUDOWLANYCH No. 1487

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class B-s1,d0
Permeability to CO ₂ Permeability to water vapour Capillary absorption and permeability to water Adhesion strength by pull-off test	$S_D > 50 \text{ m}$ Classe I, $S_D < 5 \text{ m}$ $w \le 0,1 \text{ Kg/m}^2 \text{ h}^{-0,5}$ $\ge 0,8 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**At Sassuolo, on 18/05/2020



kerakoll.com