

## kerakoll

## **DECLARATION OF PERFORMANCE No 0080**

- 1. Unique identification code of the product-type: KERAKOVER ACRILEX FLEX 1.0
- 2. Intended use/es: On external or internal walls, ceilings, columns and partitions
- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP:

System 4

System 3 for reaction to fire

5. Harmonised standard: **EN 15824:2017** 

Notified body/ies: INSTYTUT CERAMIKI I MATERIALOW BUDOWLANYCH No. 1487

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class B-s1,d0
Water vapour permeability	V <sub>2</sub>
Water absorption	<b>W</b> <sub>3</sub>
Adhesion	≥ 0,3 MPa
Durability	NPD
Thermal conductivity	λ=0,85 W/(m•k)
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**At Sassuolo, on 28/12/2020

