

## kerakoll

## **DECLARATION OF PERFORMANCE No 0208**

1. Unique identification code of the product-type: **BIOFLEX** 

2. Intended use/es:

Improved cementitious adhesive, all internal and external tiling

3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia

4. System/s of AVCP:

System 3

System 3 for reaction to fire

5. Harmonised standard: EN 12004:2007 + A1:2012

Notified body/ies: Modena Centro Prove No. 1599

Istituto Giordano No. 0407

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Bond strength as: initial tensile adhesion strength  Durability for:	≥ 1,0 N/mm²
Tensile adhesion strength after heat ageing Tensile adhesion strength after water immersion Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm² ≥ 1,0 N/mm² ≥ 1,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)** At Sassuolo, on 11/05/2017

Mofreolei

## kerakoll.com