

DECLARATION OF PERFORMANCE No 0297

1. Unique identification code of the product-type: **H40 EXTREME**
2. Intended use/es: **Improved reaction resin adhesive for all internal and external tiling**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. Importer: **Kerakoll UK Ltd - Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK.**
5. System/s of AVCP:

System 3

6. Harmonised standard: **BS EN 12004:2007 + A1:2012**

Notified body/ies: **Lucideon No. 1289**

WARRINGTON FIRE No. 0833

7. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class B2-s1, d0
Bond strength as: initial shear adhesion strength	≥ 2,0 N/mm²
Durability for: shear adhesion strength after thermal shock shear adhesion strength after water immersion	≥ 2,0 N/mm² ≥ 2,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Carl Gardner (Regional Managing Director)**

At Leyland, on 01/06/2024



www.kerakoll.com