

kerakoll

DECLARATION OF PERFORMANCE No 0328

- 1. Unique identification code of the product-type: NANOFLEX NO LIMITS
- 2. Intended use/es:

Cementitious liquid-applied (CM O1P)water impermeable product for external installations on walls, floors and swimming pools, beneath ceramic tiling (bonded with C2 adhesive in accordance with EN 12004)

- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP:

System 3 for waterproofing
System 4 for all the characteristics other than waterproofing

5. Harmonised standard: EN 14891:2012+AC:2012

Notified body/ies: Modena Centro Prove No.1599

6. Declared performance/s:

Essential characteristics	Performance
Initial tensile adhesion strength	≥ 0,5 N/mm ²
Tensile adhesion strength after water contact	≥ 0,5 N/mm²
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm²
Tensile adhesion strength after contact with lime water	≥ 0,5 N/mm²
Waterproofing	No penetration
Crack Bridging ability under standard conditions (+ 23°C)	≥ 0,75 mm
Crack Bridging ability at low temperature (- 5°C)	≥ 0,75 mm
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative)

Sassuolo 02/04/2021

Mylede