



kerakoll

DECLARATION OF PERFORMANCE No 0370

1. Unique identification code of the product-type: **GEOCALCE MULTIUSO**
2. Intended use/es: **General purpose rendering/plastering mortar (GP)**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 4
System 4 for reaction to fire
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies:-
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Adhesion Water absorption Water vapour diffusion coeff. Thermal conductivity ((λ10, dry)	$\geq 0,5$ N/mm² -FP:B W_c1 μ 13 0,54 W/mK (v.t.)
Durability (against freeze-thaw) : evaluation based on provisions valid in the intended place of use of the mortar	
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 19/04/2018

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.



kerakoll

DECLARATION OF PERFORMANCE No 0370

1. Unique identification code of the product-type: **GEOCALCE MULTIUSO**
2. Intended use/es: **Repair products for concrete, used in buildings and civil engineering works**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 2+
System 4 for reaction to fire
5. Harmonised standard: **EN 1504-3:2005**
Notified body/ies: **S.G.S. Italia No.1381**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	Class R1
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 0,8 MPa
Thermal compatibility (freeze-thaw)	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 19/04/2018

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.