



kerakoll

DECLARATION OF PERFORMANCE No 0399

1. Unique identification code of the product-type: **BENESSEREBIO**
2. Intended use/es: **Renovation mortar (R) : internal/external use.**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 4
System 4 for reaction to fire
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies:-
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Adhesion Water absorption Water vapour diffusion coeff. Thermal conductivity (λ_{10}, dry) Durability (against freeze-thaw)	$\geq 0,1 \text{ N/mm}^2$ - FP:B $\geq 0,3 \text{ Kg/m}^2$ after 24 h $\mu 5$ $0,14 \text{ W/mK}$ NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 30/01/2018

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.



kerakoll

DECLARATION OF PERFORMANCE No 0399

7. Unique identification code of the product-type: **BENESSEREBIO**
8. Intended use/es: **Thermal insulating mortar (T) : internal/external use.**
9. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
10. System/s of AVCP:
System 4
System 4 for reaction to fire
11. Harmonised standard: **EN 998-1:2016**
Notified body/ies:-
12. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Adhesion	$\geq 0,1$ N/mm² - FP:B
Water absorption	W_c1
Water vapour diffusion coeff.	μ 5
Thermal conductivity (λ_{10}, dry)	0,14 W/mK (T₂)
Durability (against freeze-thaw)	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**
At Sassuolo, on 30/01/2018

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.