

## kerakoll

## **DECLARATION OF PERFORMANCE No. 0411**

- 1. Unique identification code of the product-type: CHIUDI TRACCIA
- 2. Intended use/es: Designed general purpose masonry mortar (G) for internal and external use in elements subject to structural requirements
- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP:

System 2+

System 4 for reaction to fire

Harmonised standard: EN 998-2:2016
Notified body/ies: S.G.S. Italy No.1381

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	M 2,5
Shear bond strength	0,15 N/mm² (t.v.)
Flexural bond strengh	NPD
Contents of chloride	≤ 0,05%
Water absorption	1,20 Kg/m²min <sup>0,5</sup>
Water vapour permeability	μ 15/35 (t.v.)
Thermal conductivity	0,66 W/mK (t.v.)
Durability	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**At Sassuolo, on 27/07/2018

Myledei

## kerakoll.com