

## kerakoll

## **DECLARATION OF PERFORMANCE No 0629**

1. Unique identification code of the product-type: KLIMA HP

2. Intended use/es: General purpose rendering/plastering mortar (GP)

3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia

4. System/s of AVCP:

System 4

System 3 for reaction to fire

5. Harmonised standard: EN 998-1:2016

Notified body/ies: Istituto Giordano N°0407

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	A2 - s1, d0
Adhesion	≥0,80 N/mm² FP:B
Water absorption	W <sub>c</sub> 2
Water vapour diffusion coeff.	μ 16
Thermal conductivity	0,29 W/mK (tab. Value)
Durability (agaist freeze/thaw)	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)** At Sassuolo, on 07/12/2023



## kerakoll.com