

## kerakoll

## **DECLARATION OF PERFORMANCE No 0680**

1. Unique identification code of the product-type: H40 TECH

2. Intended use/es:

Improved cementitious adhesive for all internal and external tiling.

- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP:

System 3

5. Harmonised standard: EN 12004:2007 + A1:2012

Notified body/ies: Modena Centro Prove No. 1599

Istituto Giordano No. 0407

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2 -s1,d0
Bond strength as: initial tensile adhesion strength	≥ 1,0 N/mm²
Durability for: Tensile adhesion strength after heat ageing Tensile adhesion strength after water immersion Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm² ≥ 1,0 N/mm² ≥ 1,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative) At Sassuolo, on 23/10/2024

Melede