

DECLARATION OF PERFORMANCE No 0216

1. Unique identification code of the product-type: **ISOBUILD ECO BLOK**
2. Intended use/es: **Designed thin layer masonry mortar (T) for external use in elements subject to structural requirements**
3. Manufacturer: **Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów**
4. System/s of AVCP:
System 2+
5. Harmonised standard: **EN 998-2:2016**
Notified body/ies: **Instytut Ceramiki i Materiałów Budowlanych Nr 1487**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	M5
Initial shear strength	0,3 N/mm² (v.t.)
Flexural bond strength	NPD
Contents of chloride	≤ 0,05 %
Water absorption	0,6 Kg/(m² min^{0,5})
Water vapour permeability	μ 5/20 (v.t.)
Thermal conductivity	0,37 w/mK (v.t)
Durability	NPD
Release of dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Jacek Szczycinski (legal representative)**

At Rzgów, on 23/02/2023

