

- 1. Unique identification code of the product-type: GEOLITE
- 2. Intended use/es: Repair products for concrete, used in buildings and civil engineering works according to principles 2 (MC), 5 (PR) and 8 (IR).
- 3. Manufacturer: Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów
- 4. System/s of AVCP:

System 2+

System 4 for reaction to fire

5. Harmonised standard: EN 1504-2:2004

Notified body/ies: Sieć Badawcza Łukasiewicz - Instytut Ceramiki i Materiałów Budowlanych Nr1487

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Permeability to water vapour	Class I, S _D < 5 m
Capillary absorption and permeability to water	w < 0,1 kg*m ⁻² *h ^{-0,5}
Adhesion strength by pull-off test	≥ 2,0 N/mm²
Linear shrinkage	≤ 0,3%
Coefficient of thermal expansion	αt ≤ 30 • 10 ⁻⁶ °K ⁻¹
Abrasion resistance	weight loss < 3000 mg
Resistance to thermal shock	adhesion strength ≥ 2,0 N/mm²
Impact resistance	Class III
Release of dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Jacek Szczycinski (legal representative)

Jacob Sych



- 1. Unique identification code of the product-type: GEOLITE
- 2. Intended use/es: Repair products for concrete, used in buildings and civil engineering works according to principles 3 (CR), 4 (SS) and 7 (RP).
- 3. Manufacturer: Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów
- 4. System/s of AVCP:

System 2+

System 4 for reaction to fire

5. Harmonised standard: EN 1504-3:2005

Notified body/ies: Sieć Badawcza Łukasiewicz - Instytut Ceramiki i Materiałów Budowlanych Nr1487

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	Class R4
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 2,0 MPa
Thermal compatibility (freeze-thaw)	≥ 2,0 MPa
Capillary absorption	≤ 0,5 kg ·m ⁻² · h ^{-0,5}
Elastic modulus CC	≥ 20 GPa
Elastic modulus PCC	≥ 20 GPa
Carbonation resistance	Pass
Release of dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Jacek Szczycinski (legal representative)

Jacob Snych



- 1. Unique identification code of the product-type: GEOLITE
- 2. Intended use/es: Repair products for concrete, used in buildings and civil engineering works according to principle 4 (SS).
- 3. Manufacturer: Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów
- 4. System/s of AVCP:

System 2+

System 4 for reaction to fire

5. Harmonised standard: EN 1504-6:2007

Notified body/ies: Sieć Badawcza Łukasiewicz - Instytut Ceramiki i Materiałów Budowlanych Nr1487

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Pull-out strength displacement Chloride ion content	≤ 0,6 mm at load of 75 KN ≤ 0,05 %
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jacob Snych

Signed for and on behalf of the manufacturer by: Jacek Szczycinski (legal representative)

At Rzgów, on 23/02/2023



- 1. Unique identification code of the product-type: GEOLITE
- 2. Intended use/es: Repair products for concrete, used in buildings and civil engineering works according to principle 11 (CA).
- 3. Manufacturer: Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów
- 4. System/s of AVCP:

System 2+

System 4 for reaction to fire

5. Harmonised standard: EN 1504-7:2006

Notified body/ies: Sieć Badawcza Łukasiewicz - Instytut Ceramiki i Materiałów Budowlanych Nr1487

6. Declared performance/s:

Essential characteristics	Performance
Shear adesion Corrosion protection	Pass Pass
Release of dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jacob Snych

Signed for and on behalf of the manufacturer by: Jacek Szczycinski (legal representative)

At Rzgów, on 23/02/2023