

## DECLARATION OF PERFORMANCE No 0377

1. Unique identification code of the product-type: **AQUASTOP FLEX CM O2P**
2. Intended use/es:  
**Cementitious liquid-applied water impermeable product  
In external installation and in swimming pools, beneath ceramic tiling  
(bonded with C2 adhesive in accordance with EN 12004)**
3. Manufacturer: **Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów**
4. System/s of AVCP:  
**System 3 for waterproofing  
System 4 for all the characteristics other than waterproofing**
5. Harmonised standard: **EN 14891:2012+AC:2012**  
Notified body/ies: **Modena Centro Prove No.1599**
6. Declared performance/s:

Essential characteristics	Performance
<b>Initial tensile adhesion strength</b>	<b>≥0,5 N/mm<sup>2</sup></b>
<b>Tensile adhesion strength after water contact</b>	<b>≥0,5 N/mm<sup>2</sup></b>
<b>Tensile adhesion strength after heat ageing</b>	<b>≥0,5 N/mm<sup>2</sup></b>
<b>Tensile adhesion strength after contact with lime water</b>	<b>≥0,5 N/mm<sup>2</sup></b>
<b>Waterproofing</b>	<b>No penetration</b>
<b>Tensile adhesion strength after contact with chlorinated water</b>	<b>≥0,5 N/mm<sup>2</sup></b>
<b>Crack Bridging ability under standard conditions</b>	<b>≥0,75 mm</b>
<b>Crack Bridging ability at very low temperature (-20 °C)</b>	<b>≥0,75 mm</b>
<b>Tensile adhesion strength after freeze-thaw cycles</b>	<b>≥0,5 N/mm<sup>2</sup></b>

**Release of dangerous substances: See SDS**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Jacek Szczycinski (General Manager)**

At Rzgów, 22/02/2023



## DECLARATION OF PERFORMANCE No 0377

1. Unique identification code of the product-type: **AQUASTOP FLEX**
2. Intended use/es:  
**Coating for surface protection of concrete structures according to principles 1(PI), 2 (MC), and 8 (IR).**
3. Manufacturer: **Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów**
4. System/s of AVCP: **System 2+ and System 4 for reaction to fire**
5. Harmonised standard: **EN 1504-2:2004**  
Notified body/ies: **Instytut Ceramiki i Materiałów Budowlanych Nr1487**
6. Declared performance/s:

Essential characteristics	Performance
<b>Reaction to fire</b>	<b>Class F</b>
<b>Permeability to CO<sub>2</sub></b> <b>Permeability to water vapour</b> <b>Capillary absorption and permeability to water</b> <b>Adhesion strength by pull-off test</b>	<b>S<sub>D</sub> &gt; 50 m</b> <b>Class I, S<sub>D</sub> &lt; 5 m</b> <b>w &lt; 0,1 kg*m<sup>-2</sup> *h<sup>-0,5</sup></b> <b>≥ 0,8 N/mm<sup>2</sup></b>

**Release of dangerous substances: See SDS**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Jacek Szczycinski (General Manager)**

At Rzgów, 22/02/2023

*Jacek Szczycinski*