

**DECLARATION OF PERFORMANCE No 0566**

1. Unique identification code of the product-type:  
**Aquaform Pro profil, Aquaform Pro NZ90, Aquaform Pro NW90, Aquaform Pro NZ135, Aquaform Pro NW135, Aquaform Pro L, Aquaform Pro profil boczny, Aquaform Pro NZ90-BL, Aquaform Pro NZ90-BP**
2. Intended use/es:  
**Eaves profiles for terraces and balconies**
3. Manufacturer:  
**Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów**
4. System/s of AVCP:  
**System 3**
5. European Assessment Document:  
**EAD 220008-00-0402**  
European Technical Assessment:  
**ETA-22/0190 z 14/03/2022**  
Technical Assessment Body:  
**Instytut Techniki Budowlanej, ul. Filtrowa 1, 00-611 Warszawa, No 1488**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2-s1,d0
Coating thickness	≥ 60 µm
Adhesion	0
Indentation	≥ 80
Acetic acid salt spray resistance, testing time: 1000 hours	No blistering in excess of 2 (S2) according to ISO 4628-2. An infiltration of maximum 16 mm <sup>2</sup> is allowed over a scratch length of 100 mm but the length of any single infiltration shall not exceed 4 mm
Resistance to humid atmospheres containing sulphur dioxide (0,2 l SO <sub>2</sub> - 24 cycles)	No infiltration exceeding 1 mm on both sides of the scratch, and no change in colour or blisters in excess of 2 (S2) according to ISO 4628-2
note: the coating has a QUALICOAT mark corresponding to the abovementioned performance	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer: **Jacek Szczycinski (legal representative)**

*Jacek Szczycinski*

At Rzgów, on 22/02/2023