

## DECLARATION OF PERFORMANCE No 0663

1. Unique identification code of the product-type: **H40 GEL**  
Intended use/es:  
**Improved cementitious adhesive for all internal and external tiling.**
2. Manufacturer: **Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów**
3. System/s of AVCP:  
**System 3**  
**System 3 for reaction to fire**
4. Harmonised standard: **EN 12004:2007 + A1:2012**  
Notified body/ies: **SIEĆ BADAWCZA ŁUKASIEWICZ - INSTYTUT CERAMIKI I MATERIALOW BUDOWLANYCH No. 1487**
5. Declared performance/s:

Essential characteristics	Performance
<b>Reaction to fire</b>	<b>Class A2-s1,d0/A2fl-s1</b>
<b>Bond strength expressed as:- initial tensile adhesion strength</b>	<b>≥ 1,0 N/mm<sup>2</sup></b>
<b>Durability of bond strength against climate/heat ageing action expressed as: tensile adhesion strength after heat ageing</b>	<b>≥ 1,0 N/mm<sup>2</sup></b>
<b>Durability of bond strength against water/humidity action expressed as: tensile adhesion strength after water immersion</b>	<b>≥ 1,0 N/mm<sup>2</sup></b>
<b>Durability of bond strength against freeze-thaw cycles expressed as: tensile adhesion strength after freeze-thaw cycles</b>	<b>≥ 1,0 N/mm<sup>2</sup></b>
<b>Release of dangerous substances</b>	<b>NPD</b>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Jacek Szczycinski (legal representative)**



At Rzgów, on 01/10/2024