

Fast Clean

Professional cleaning wipes.
Rapid drying, degreasing detergent for the
preparation of substrates, smoothing of
joints and post-installation cleaning.



1. Large double-face wipes:
 - an abrasive surface for stubborn stains
 - a smooth surface for final cleaning
2. High degreasing power, non-irritating
3. With vitamin E, Aloe Vera and glycerin
4. To be used without water or soap, they do not require rinsing and leave no residue
5. Dermatologically tested product

Areas of application

→ Fast Clean wipes work effectively on all types of recent dirt (fresh products): grouts, glues, adhesives, polyurethane foams... and also on grease, lubricants, bitumen, paints, inks, resins, ballpoint pens...

Cleaning of hands, tools, and worktops. Soaked in a powerful formula enriched with vitamin E, Aloe Vera and glycerin, making the skin smooth after use. With a pleasant citrus scent, they easily eliminate odours from treated products.

Certificates and marks



Technical Data compliant with Kerakoll Quality Standard

Composition	PP/Viscose
Appearance	abrasive/smooth double surface
Weight	45 g/m ²
Tolerance	±12%
Dimensions	250x300 mm (bucket 130) – 270x300 mm (bucket 70)
Impregnation solution	
Appearance	clear liquid of a colour between transparent and pale yellow
pH	5,0 ± 0,5
Density at +20 °C	1,00 ± 0,05
Storage temperature	between +5 °C and +40 °C
Fragrance	citrus fruits
Shelf life	≈ 12 months in the original packaging, unopened and protected against damp
Pack	bucket with 130 wipes – 60 cartons of 4 buckets per pallet bucket with 70 wipes – 64 cartons of 4 buckets per pallet

Warning

→ Store in a ventilated area at a temperature not exceeding +30 °C

→ for any other issues, contact the Kerakoll Worldwide Global Service +33 (0) 4 72 89 06 80 - globalservice@kerakoll.com

The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in June 2024 (ref. GBR Data Report - 06.24); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.