

Fuga-Wash

Detergent to be used as an additive in water used to clean Fugalite.

Fuga-Wash, when used as an additive in cleaning water, has a specific detergent action that does not damage ceramic tile, porcelain tile and natural stone surfaces.



Rating 4

1. Facilitates cleaning of covering materials
2. Keeps the sponge cleaner
3. Cleans thoroughly, no need to rinse
4. Improves the surface finish of the grout
5. Suitable for all surfaces

- × VOC Low Emission
- ✓ Water Based
- ✓ Solvent ≤ 15 g/kg
- ✓ Low Ecological Impact
- ✓ Health Care

Areas of application

→ Use

To be added to the water used to clean Fugalite Color and Fugalite Invisible.

Substrates:

- ceramic, porcelain tiles
- glass mosaic, marble and natural stone

Do not use to remove residues and streaks of hardened grout.

Instructions for use

→ Preparation of substrates

The coating materials must first be cleaned to remove any dust. Fugalite Color and Fugalite Invisible must still be fresh.

→ Preparation

Fuga-Wash is a ready-to-use transparent fluid that can be diluted with water in any ratio. Shake the bottle well before opening in order to redisperse the liquid evenly. Pour one measuring cap (approx. 50 ml) for every 5 litres of water in the cleaning tray.

→ Application

Begin cleaning the tilework when the grout is still fresh. On completion, pour Fuga-Wash into the cleaning tray in the quantities indicated, then clean up the surface using a thick, large-sized damp sponge, preferably made of cellulose, to avoid removing grout from the joints. Use

circular movements to soften the film of grout on the tiles and finish cleaning the joint surface. Specific high-dispersion polymers ensure all grout residues are removed using only a small amount of water. The use of an excessive amount of water when cleaning would impair the final chemical resistances. Rinse frequently and make sure clean water is used at all times, using appropriate trays and grills with cleaning rollers. If necessary, replace the sponge or felt cleaning pad when saturated with grout. Final cleaning should be done, by sponge applied in a diagonal directions to avoid material coming out from the joints. Wipe the cleaned surface again with a dry cloth to make sure it is completely clean and there are no streaks of resin remaining.

→ Cleaning

Residues of Fuga-Wash can be cleaned from tools by rinsing them thoroughly with water.

Abstract

To be added to the water used to clean Fugalite Color and Fugalite Invisible from ceramic tiles, porcelain tiles, glass mosaic, marble and natural stone use an eco-friendly, water-based detergent, Eco 4 GreenBuilding Rating, such as Fuga-Wash by Kerakoll Spa.

Technical Data compliant with Kerakoll Quality Standard


Appearance	Transparent liquid
Specific weight	≈ 1 kg/dm ³
Shelf life	≈ 24 months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Pack	bottles 1.5 l
Water dilution ratios	All ratios recommended dosage 1 measuring cap every 5 l of water in the washing tray
pH	≈ 7
Temperature range for application	from +5 °C to +35 °C
Coverage	≈ 100 – 200 m ² /1 l

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate and of the materials laid.

Warning

- Product for professional use
- abide by any standards and national regulations
- store and use at a temperature above +5 °C.
- Protect from frost
- do not leave cans or bottles open, even during use

- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in October 2023 (ref. GBR Data Report - 10.23); please note that additions and/or amendments to this information may be made over time by KERAKOLL Spa; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.