

# Kerakover Activ

Water-based restoring product.

Kerakover Activ, based on active anti-biodeteriorating agents, is suitable for preserving surfaces affected by deposits and colonies of mould, algae, fungi and lichen.



## Rating 3

1. With preventive and slowing action against bacteria, algae, fungi and lichens
2. Odourless
3. Easy to apply
4. Internal, external

- × VOC Low Emission
- ✓ Water Based
- ✓ Solvent  $\leq 15$  g/kg
- × Low Ecological Impact
- ✓ Health Care

---

## Areas of application

### → Use

- natural stone, artificial stone and cotto-covered wall surfaces, both for internal and external use
- fine stone or unusual surfaces, such as artistic moulded ones

- surfaces already covered with synthetic finishes or plastic coatings
  - gypsum surfaces
- For internal and external use.

Do not use in the presence of rising damp.

---

## Instructions for use

### → Preparation of substrates

Surfaces to be treated must be solid and stable to prevent fractures from leaving some areas untreated. Protect all surfaces that could be damaged.

For the treatment of substrates other than those mentioned and for additional information on the types of intervention to be carried out, we recommend to consult Kerakoll's Guide to decorating and preparing substrates.

### → Preparation

Kerakover Activ is ready-to-use and does not require dilution with either solvents or water.

### → Application

First apply a liberal coat of the product with a brush or low pressure spray gun to the surface to be restored and leave it to set for 24 hours.

External use: clean the affected surfaces with water, preferably using a high-pressure washer, in order to remove all traces of deposits.

Internal use: rinse the affected surfaces with water and clean using brushes and scrapers to completely remove all traces of deposits.

Repeat the application of Kerakover Activ as necessary for tougher concentrations or remaining streaks or deposits, finishing off by washing as before.

When repairing fine moulded, ornate and internal surfaces, apply the product with a brush or low pressure spray gun then rinse using water, cleaning at the same time with broomcorn brushes or scrapers until all traces of deposits have been removed.

Conditions required for decorating are ambient and substrate temperatures between +5 °C and +30 °C and a relative ambient humidity lower than 80%.

Do not apply when the substrate is directly exposed to sunlight or in heavy wind.

After application, external surfaces must be protected from rain for 24 hours.

### → Cleaning

Residual traces of Kerakover Activ can be removed from tools using water immediately after use.

---

## Special notes

→ This product can cause irritation; in case of contact with the skin, rinse immediately with

soap and water.

# Certificates and marks



\* Émission dans l'air intérieur Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

## Abstract

Restoring product for internal and external surfaces affected by deposits and colonies of mould, algae, fungi and lichen, applying with brush, roller or low pressure spray a ready-to-use, water-based solution of active anti-biodeteriorating agents with a low solvent content, such as Kerakover Activ by Kerakoll Spa, GreenBuilding Rating 3.

### Technical Data compliant with Kerakoll Quality Standard

Appearance	straw-coloured liquid
Volumetric mass	≈ 1 kg/l
Pack	5 – 10 l cans / 1 l bottles
Shelf life	≈ 18 months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +5 °C to +30 °C
Reaction time	≈ 12 h
Coverage when applying two coats for a fine-texture, two-coat finish	≈ 0,2 – 0,3 l/m <sup>2</sup>

Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

## Warning

- Product for professional use
- abide by any standards and national regulations
- use at temperatures between +5 °C and +30 °C
- make sure the substrate is not frozen
- protect surfaces from direct sunlight and wind
- protect from rain and strong humidity for 24 hours following application
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in September 2023 (ref. GBR Data Report - 09.23); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.