

# Keradecor Prontofix

Stabilizing primer based on pure powerful high-binding acrylic resins.

Keradecor Prontofix is suitable for cortical consolidation, guaranteeing the uniform absorption and colour of the next decorative cycle. For internal use.



## Rating 3

1. Ready-to-use
2. High consolidating power
3. Excellent substrate uniforming power
4. Easy to apply with a brush, roller or spray

- × VOC Low Emission
- ✓ Water Based
- ✓ Solvent  $\leq 15$  g/kg
- × Low Ecological Impact
- ✓ Health Care

---

## Areas of application

### → Use

Stabilizing product for internal use on:

- lime- or cement-based plasters
- cement-lime mortar
- concrete
- gypsum- or scagliola-based plasters
- lime-based paints, water-based washable and breathable paints, absorbent tempera paints, all well-anchored to the substrate
- plasterboard

For internal use.

Do not use in the presence of rising damp.

---

## Instructions for use

### → Preparation of substrates

Porous substrates with a limited level of cohesion must in any case be compact and absorbent, free from dust, oil or efflorescence, with no loose debris or flaky parts.

On surfaces coated with synthetic finishes, paint or plastic coatings, remove all partially deteriorated sections that are fragmenting or separating from the substrate. The substrate must be stable, non-deformable and with no fracturing cracks.

In the presence of mould, first treat with Kerakover Activ biocide. The substrate must be dry at the time of application. For the treatment of substrates other than those mentioned and for additional information on the types of intervention to be carried out, we recommend to consult Kerakoll's Guide to decorating and preparing substrates.

### → Preparation

Keradecor ProntoFix is ready-to-use.

Always remix the product before application.

### Application

→ When applying the product preferably use a short bristle, synthetic fibre roller or a brush.

Apply one or more coats avoiding drips, depending on the porosity and nature of the substrate to be consolidated or evened out. Conditions required for decorating are ambient and substrate temperatures between +5 °C and +30 °C and a relative ambient humidity lower than 80%.

Wait 6 hours before the subsequent paint cycle, and in any event until the product has fully dried.

### → Cleaning

Keradecor ProntoFix can be cleaned from tools by washing them using water before the product hardens.

---

## Special notes

→ On very compact and poorly absorbent surfaces, a surface film with a glossy effect may form: it could cause the paint to slip.

# Certificates and marks



\* Émission dans l'air intérieur Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

## Abstract

Fixing and evening up absorption of internal surfaces, by application using a brush, roller or spray of a water-based pure acrylic resin primer with a low solvent content, such as Keradecor Prontoifix by Kerakoll Spa, GreenBuilding Rating 3.

### Technical Data compliant with Kerakoll Quality Standard


|                                       |   |
|---------------------------------------|---|
| Appearance                            | milky white   |
| Volumetric mass                       | ≈ 1 kg/l  |
| Chemical nature                       | acrylic   |
| Pack                                  | 1 – 5 – 10 l cans   |
| Shelf life                            | ≈ 24 months from production in the original sealed packaging              |
| Warning                               | protect from frost, avoid direct exposure to sunlight and sources of heat |
| Viscosity                             | 25 s – Iso 3 flow cup   |
| Temperature range for application     | from +5 °C to +30 °C  |
| Humidity of the substrate             | ≤ 6%  |
| Waiting time between subsequent coats | ≥ 6 hrs   |
| Average coverage per single coat      | ≈ 0,1 – 0,15 l/m <sup>2</sup>   |

Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

## Warning

- Product for professional use
- abide by any standards and national regulations
- apply one or more coats, depending on substrate
- if necessary, ask for the safety data sheet

→ for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in May 2023 (ref. GBR Data Report - 06.23); please note that additions and/or amendments to this information may be made over time by KERAKOLL Spa; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.