

Keradecor Solmix Universal

Thinner high solvent power and slow evaporation.

Keradecor Solmix Universal is suitable for products which need a high solvent power or a slow evaporation time. Internal, external.



1. Slow evaporation
2. High solvent power
3. Suitable for diluting: Keradecor Sintcrom, Keradecor Zinkover



Rating 0

Product with none of the requisites of the GreenBuilding Rating, must be used with care.

Kerakoll undertakes to improve the ratings of Rating zero materials and products.

Areas of application

→ Use

Thinner for products which need a high solvent power or a slow evaporation time.

Suitable for diluting:

- Keradecor Sintcrom
- Keradecor Zinkover

Do not use (it must not be used) to dilute quick-drying products or products based on chlorinated rubber resins.

Instructions for use

→ Preparation

Dilute as indicated on the reference products. Keradecor Solmix Universal is ready-to-use.

→ Cleaning

Keradecor Solmix Universal can be used to clean tools.

Special notes

→ Ensure suitable ventilation when using indoors.

→ Do not smoke or do not eat during use.

→ Keradecor Solmix Universal is flammable.

Certificates and marks



* Émission dans l'air intérieur Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

Abstract

Dilution with thinner for products which need a high solvent power and a slow evaporation time, like Keradecor Zinkover and Keradecor Sintcrom, such as Keradecor Solmix Universal by Kerakoll Spa.

Technical Data compliant with Kerakoll Quality Standard

Appearance	Transparent liquid
Volumetric mass	≈ 0.875 kg/l
Chemical nature	aromatic hydrocarbons
Pack	1 – 5 l drums
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +5 °C to +30 °C

Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

Warning

- Product for professional use
 - abide by any standards and national regulations
 - use at temperatures between +5 °C and +30 °C
 - do not mix with acids or alkalis
- if necessary, ask for the safety data sheet
 - for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in July 2023 (ref. GBR Data Report – 07.23); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.