

Keradecor Zinkover

Base and finish coat glaze, resistant to atmospheric agents, excellent coverage and easy to apply with a brush.

Keradecor Zinkover, highly protective and containing solvent-based synthesis resins, is suitable for the preparation of galvanized surfaces. Provides a high degree of protection from the effects of the weather and marine environments. Internal, external.



1. Ideal for galvanized surfaces
2. High coverage
3. Easy to apply with a brush, roller or spray.

Rating 0

Product with none of the requisites of the GreenBuilding Rating, must be used with care.

Kerakoll undertakes to improve the ratings of Rating zero materials and products.

Areas of application

→ Use

Glaze for:

- galvanized sheet metal (guttering, down spouts, shutters, doors and windows, garage doors, gates, wire fences, fences, guard rails, awnings, trellises)
- aluminium (guttering, down spouts, doors and windows)

For internal and external use.

Do not use on wet surfaces.

Instructions for use

→ Preparation of substrates

New galvanized surfaces: degrease thoroughly using Keradecor Solmix Universal thinner. Apply Keradecor Zinkover directly, adjusting dilution with Keradecor Solmix Universal, as required for application by brush, conventional and airless spray.

Slightly rusted galvanized surfaces: remove the rust completely by sanding and apply Keradecor Sintcrom. Apply Keradecor Zinkover, adjusting dilution with Keradecor Solmix Universal, as required for application by brush, conventional and airless spray.

Galvanized surfaces painted with deteriorated products: remove all traces of the existing paintwork and wash thoroughly with Keradecor Solmix Universal. Apply Keradecor Zinkover directly, adjusting dilution with Keradecor Solmix Universal, as required for application by brush, conventional and airless spray.

All the above mentioned substrates must be clean, dry and free from oil and grease.

For the treatment of substrates other than those mentioned and for additional information on the types of intervention to be carried out, we recommend to consult Kerakoll's Guide to decorating and preparing substrates.

→ Preparation

Always remix the product before application.

→ Application

Keradecor Zinkover must be applied carefully over the whole surface using a brush, roller or spray, first diluting by from 5% to 15% with Keradecor Solmix Universal thinner, according to the application method used. When applying by brush or roller, dilute Keradecor Zinkover with Keradecor Solmix Universal in a percentage of 5 – 10%. When applying by spray, dilute Keradecor Zinkover with Keradecor Solmix Universal in a percentage of 10 – 15%.

Application, particularly external application, requires two coats of the product to be laid, at a distance of at least 24 hours.

Conditions required for decorating are ambient and substrate temperatures between +5 °C and +30 °C and relative ambient moisture lower than 80%.

In cases where different lots of coloured product are used, or when completing a job in which a tintometer has been used, it is advisable to mix the various quantities together so as to avoid slight differences in tone.

→ Cleaning

Residual traces of Keradecor Zinkover can be removed from tools using Keradecor Solmix Universal before the product hardens.

Special notes

→ Do not apply the product or suspend its application in the presence of wind, smoke or dust, protect surfaces from rain or night-time

condensation until the paint layer has completely dried.

→ Keradecor Zinkover is flammable.

Certificates and marks



* Émission dans l'air intérieur Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

Abstract

Protection of external and internal surfaces, by application using a brush, roller or spray of high coverage base coat suitable for the preparation of galvanized surfaces, containing synthesis resins, such as Keradecor Zinkover by Kerakoll Spa.

Technical Data compliant with Kerakoll Quality Standard

| | |
|---|---|
| Appearance | white glaze |
| Volumetric mass | ≈ 1.3 kg/l |
| Chemical nature | special resins |
| Pack | 0.75 – 2.5 l tins |
| Shelf life | ≈ 24 months from production in the original sealed packaging |
| Warning | Protect from frost, avoid direct exposure to sunlight and sources of heat |
| Temperature range for application | from +5 °C to +30 °C |
| Humidity of the substrate | ≤ 6% |
| Waiting time between 1 st and 2 nd coat | ≥ 24 hrs |
| Coverage for 2 coats | ≈ 0.1 – 0.15 l/m ² |

Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

Warning

- Product for professional use
- abide by any standards and national regulations
- use at temperatures between +5 °C and +30 °C
- flammable product
- make sure the substrate is not frozen
- Do not add binders or additives
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in December 2022 (ref. GBR Data Report – 12.22); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.