

# Proman

Eco-friendly, breathable barrier cream to protect the hands from the most common aggressive agents.

Proman creates a breathable barrier to protect the hands from oil, grease, varnishes, resins, adhesives, tar, petrol, silicon, solvents and synthetic products in general. Can be easily cleaned at the end of application with soap and water.



1. Dermatologically-tested
2. Forms a protective, breathable barrier
3. Easy to remove

---

## Areas of application

→ Intended use:

Protection of the hands from dirt and aggressive substances such as solvents, varnishes, glues,

resins, adhesives, tar, petrol, silicon, oils, greases, synthetic products.

---

## Instructions for use

→ Application

Before starting work, evenly spread a sufficient quantity of cream on the hands without neglecting the finger nails and the areas around them.

After a few minutes, the product will dry forming an thin invisible barrier on the skin that suitably protects from the substances indicated above.

A greater protection can be obtained with a double application of the product. Periodically renew the application for jobs of a long duration.

→ Cleaning

To remove any dirt remaining on the hands and to remove the film of barrier cream at the end of work only needs a wash with lukewarm water scrubbing forcibly with soap.

---

## Special notes

→ Proman protective film is not sticky and does not leave prints.

→ Does not make the hands sweat.  
→ it is a dermatologically tested product.

---

### Technical Data compliant with Kerakoll Quality Standard

Appearance	white coloured paste
Pack	500 ml tin
Shelf life	≈ 24 months from the date of production in original and intact packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
pH	neutral (7)
Temperature range for application	from +10 °C to +30 °C
Drying	≈ 5 mins
Coverage	≈ 100 applications with one pot

---

# Warning

- Product for professional use
- abide by any standards and national regulations
- if necessary, ask for the safety data sheet

→ for any other issues, contact the Kerakoll  
Worldwide Global Service +39 0536 811 516 -  
globalservice@kerakoll.com

<b>Kerakoll Quality System</b>	<b>Kerakoll Quality System</b>	<b>Kerakoll Quality System</b>
ISO 9001 02811FED 1710/0327	ISO 14001 02811FED 18586-E	ISO 45001 02811FED 18586-I

The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in December 2022; please note that additions and/or amendments to this information may be made over time by KERAKOLL Spa; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.