

Silocera

Eco-friendly wax to maintain hardwood floors treated with Oil-Pur.

Silocera makes it easy to maintain wood floors with a wax finish or with oil-urethane based finishes thanks to the mix of different hard waxes.



SLC
TECHNOLOGY



Rating 2

1. Easy to apply
2. Can be polished with machine polisher
3. Revitalizes and restores surface shine
4. Forms a water-repellent protective layer

- × VOC Low Emission
- × Water Based
- × Solvent ≤ 80 g/kg
- ✓ Low Ecological Impact
- ✓ Health Care

Areas of application

→ Intended use:

Maintenance of wooden floors treated with Oil-Pur.

Interior floors

Do not use on unvarnished and untreated wood floors, on various coated wood floors and prefinished hardwood floors.

Instructions for use

→ Preparation of substrates

Carefully clean the wood floor with SuperSoap (according to the instructions supplied on the technical data sheet). If necessary, remove any resistant stains, or old layers of wax with Diluente Oil.

→ Preparation

The product is ready-to-use. Shake the container before use.

→ Application

Evenly apply a thin layer of Silocera with a clean woollen or cotton cloth, or with a wax applicator. After it is completely dry, polish with a soft cloth or with a polishing machine.

→ Cleaning

Clean the residues of Silocera with Diluente Oil when the product is fresh.

Special notes

- To give an even effect, apply layers of uniform thickness and follow the recommended quantities
- Use Super Soap according to the instructions provided in the product technical data sheet to clean floors that have been treated with Silocera

- For the maintenance of floors treated with Silocera: repolish the surface with a cotton cloth or with a polishing machine to renew the shine and to eliminate any marks and prints, apply Silocera and polish to regenerate the surface protection layer.


Technical Data compliant with Kerakoll Quality Standard

Appearance	White liquid
Pack	1 l tins
Shelf life	≈ 12 months from the date of production in original and intact packaging, protect from humidity
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	≥ +10 °C
Suitable for overlaying	≈ 1 hr
Coverage	≈ 10 – 20 ml/m ² per coat

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate.

Warning

- Product for professional use
- abide by any standards and national regulations
- ventilate premises adequately to facilitate drying
- do not walk over or cross wet flooring until it has completely dried
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in June 2023 (ref. GBR Data Report - 06.23); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.